

	SAFETY DATA SHEET	Page : 1 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
 Trade name/designation : Verado Silver Enamel Spray Paint
 Product code : 92-802878020, 92-8M0132061
 Vaporizer : Aerosol
 Document no. : 766-01-0329S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
 Main use category : Industrial use, Professional uses, Consumer use
 Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Brunswick Marine EMEA
 Parc industriel de Petit-Rechain, Avenue Mercury 8
 4800 Verviers - Belgium
 T +32 (0)87 32 32 11
bme.compliance@brunswick.com

1.4. Emergency telephone number

Emergency number : 0032 3 575 55 55
 This telephone number is available 24 hours per day, 7 days per week.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	+353 1 809 21 66 (public, 8am - 10pm, 7/7) +353 01 809 2566 (Professionals, 24/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
 Eye Irrit. 2 H319
 STOT SE 3 H336

Full text of hazard classes and H-statements : see section 16

	SAFETY DATA SHEET	Page : 2 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word :

Danger

Hazardous ingredients :

acetone, propan-2-one, propanone

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P271 - Use only outdoors or in a well-ventilated area.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 - Dispose of contents/container to an approved waste disposal plant.

Extra phrases :

EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Other hazards :

Vapours may form explosive mixture with air. Results of PBT and vPvB assessment : Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index) 606-001-00-8	40 - 45	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index) 601-003-00-5	15 - 20	Flam. Gas 1, H220 Press. Gas (Liq.), H280
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index) 601-022-00-9	5-<10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index) 601-004-00-0	5 - 10	Flam. Gas 1, H220 Press. Gas (Liq.), H280
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index) 607-025-00-1	1-<10	Flam. Liq. 3, H226 STOT SE 3, H336
Ethyl 3-ethoxypropanoate	(CAS-No.) 763-69-9 (EC-No.) 212-112-9	1 - 5	Flam. Liq. 3, H226

	SAFETY DATA SHEET	Page : 3 / 27
		Revision nr : 1.1
		Issue date : 02/03/2017
	Verado Silver Enamel Spray Paint	Supersedes : 28/04/2015
		766-01-0329S

ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index) 601-023-00-4	1 - 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
--------------	---	-------	---

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person or a person with cramps. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance. Treat symptomatically.
Inhalation	: Remove person to fresh air and keep comfortable for breathing. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Take off contaminated clothing. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause drowsiness or dizziness. The following symptoms may occur: Irritation. Sore throat. Mental confusion. Headache. Dizziness. Drowsiness. Unconsciousness.
Skin contact	: The following symptoms may occur: Repeated exposure may cause skin dryness or cracking.
Eyes contact	: Causes serious eye irritation. The following symptoms may occur: erythema (redness). Blurred vision. Pain.
Ingestion	: The following symptoms may occur: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry extinguishing powder. Water spray. Alcohol resistant foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	: Extremely flammable aerosol. Ignition risk. Vapours are heavier than air and may spread along floors. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Aerosol cans may rupture and become projectiles. In use, may form flammable/explosive vapour-air mixture. Do not spray on a naked flame or any incandescent material. On heating there is a risk of a build-up of pressure in hermetically sealed containers or tanks.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
Other information	: Do not allow run-off from fire-fighting to enter drains or water courses.

	SAFETY DATA SHEET	Page : 4 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate personnel to a safe area. Stay upwind/keep distance from source. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Leave evaporate and disperse. Clean-up methods - small spillage: Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite or powdered limestone. Collect in closed and suitable containers for disposal. Dispose of waste product or used containers according to local regulations.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with combustibles/... See also section 10. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains. Obtain special instructions before use. (Do not handle until all safety precautions have been read and understood.). Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurised container. May burst if heated.

Hygiene measures

: Keep good industrial hygiene. Wash hands immediately after handling the product. When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Separate working clothes from town clothes. Take off contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Flammable aerosols. Store in a dry, cool and well-ventilated place. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. Bund storage facilities to prevent soil and water pollution in the event of spillage. Protect from sunlight. Remove all sources of ignition. Keep at temperature not exceeding 50. Store locked up.

Packaging materials

: Keep only in the original container.

7.3. Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone, propan-2-one, propanone (67-64-1)		
EU	IOELV TWA (mg/m ³)	1210 mg/m ³
EU	IOELV TWA (ppm)	500 ppm

	SAFETY DATA SHEET	Page : 5 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

acetone, propan-2-one, propanone (67-64-1)		
Austria	MAK (mg/m ³)	1200 mg/m ³
Austria	MAK (ppm)	500 ppm
Austria	MAK Short time value (mg/m ³)	4800 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Limit value (mg/m ³)	1210 mg/m ³
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m ³)	2420 mg/m ³
Belgium	Short time value	1000 ppm
Bulgaria	OEL TWA (mg/m ³)	600 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1400 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	1210 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	500 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	3620 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	1500 ppm
Cyprus	OEL TWA (mg/m ³)	1210 mg/m ³
Cyprus	OEL TWA (ppm)	500 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	800 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	600 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	250 ppm
Estonia	OEL TWA (mg/m ³)	1210 mg/m ³
Estonia	OEL TWA (ppm)	500 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1200 mg/m ³
Finland	HTP-arvo (8h) (ppm)	500 ppm
Finland	HTP-arvo (15 min)	1500 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	630 ppm
France	VME (mg/m ³)	1210 mg/m ³ (restrictive limit)
France	VME (ppm)	500 ppm (restrictive limit)
France	VLE (mg/m ³)	2420 mg/m ³ (restrictive limit)
France	VLE (ppm)	1000 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1200 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 (BGW)	80 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift
Gibraltar	8h mg/m ³	1210 mg/m ³
Gibraltar	8h ppm	500 ppm
Greece	OEL TWA (mg/m ³)	1780 mg/m ³
Greece	OEL STEL (mg/m ³)	3560 mg/m ³
Hungary	AK-érték	1210 mg/m ³
Hungary	CK-érték	2420 mg/m ³ (Substances with European indicative limits (96/94/EC, 2000/39/EC, 2006/15/EC, 2009/161/EU), which currently has no peak limit concentration. In these cases, Annex 3.1. should be used exercised)

	SAFETY DATA SHEET	Page : 6 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

acetone, propan-2-one, propanone (67-64-1)		
Ireland	OEL (8 hours ref) (mg/m ³)	1210 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	500 ppm
Ireland	OEL (15 min ref) (mg/m ³)	3630 mg/m ³ (calculated)
Ireland	OEL (15 min ref) (ppm)	1500 ppm (calculated)
Italy	OEL TWA (mg/m ³)	1210 mg/m ³
Italy	OEL TWA (ppm)	500 ppm
Latvia	OEL TWA (mg/m ³)	1210 mg/m ³
Latvia	OEL TWA (ppm)	500 ppm
Lithuania	IPRV (mg/m ³)	1210 mg/m ³
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m ³)	2420 mg/m ³
Lithuania	TPRV (ppm)	1000 ppm
Luxembourg	OEL TWA (mg/m ³)	1210 mg/m ³
Luxembourg	OEL TWA (ppm)	500 ppm
Malta	OEL TWA (mg/m ³)	1210 mg/m ³
Malta	OEL TWA (ppm)	500 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	1210 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	2420 mg/m ³
Poland	NDS (mg/m ³)	600 mg/m ³
Poland	NDSch (mg/m ³)	1800 mg/m ³
Portugal	OEL TWA (mg/m ³)	1210 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	500 ppm (indicative limit value)
Portugal	OEL STEL (ppm)	750 ppm
Romania	OEL TWA (mg/m ³)	1210 mg/m ³
Romania	OEL TWA (ppm)	500 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	1210 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	500 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	2420 mg/m ³
Slovenia	OEL TWA (mg/m ³)	1210 mg/m ³
Slovenia	OEL TWA (ppm)	500 ppm
Spain	VLA-ED (mg/m ³)	1210 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	500 ppm (indicative limit value)
Sweden	nivågränsvärde (NVG) (mg/m ³)	600 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	250 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	1200 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	500 ppm
United Kingdom	WEL TWA (mg/m ³)	1210 mg/m ³
United Kingdom	WEL TWA (ppm)	500 ppm
United Kingdom	WEL STEL (mg/m ³)	3620 mg/m ³
United Kingdom	WEL STEL (ppm)	1500 ppm
Norway	Grenseverdier (AN) (mg/m ³)	295 mg/m ³
Norway	Grenseverdier (AN) (ppm)	125 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	368,75 mg/m ³ (value calculated)

	SAFETY DATA SHEET	Page : 7 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

acetone, propan-2-one, propanone (67-64-1)		
Norway	Grenseverdier (Korttidsverdi) (ppm)	1529,25 ppm (value calculated)
Switzerland	VME (mg/m ³)	1200 mg/m ³
Switzerland	VME (ppm)	500 ppm
Switzerland	VLE (mg/m ³)	2400 mg/m ³
Switzerland	VLE (ppm)	1000 ppm
Australia	TWA (mg/m ³)	1185 mg/m ³
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m ³)	2375 mg/m ³
Australia	STEL (ppm)	1000 ppm
Canada (Quebec)	VECD (mg/m ³)	2380 mg/m ³
Canada (Quebec)	VECD (ppm)	1000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1190 mg/m ³
Canada (Quebec)	VEMP (ppm)	500 ppm
USA - ACGIH	ACGIH TWA (ppm)	250 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm
USA - IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
propane (74-98-6)		
Austria	MAK (mg/m ³)	1800 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3600 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Limit value (ppm)	1000 ppm (gas)
Bulgaria	OEL TWA (mg/m ³)	1800 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	1800 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Estonia	OEL TWA (mg/m ³)	1800 mg/m ³
Estonia	OEL TWA (ppm)	1000 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2000 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1100 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1800 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Greece	OEL TWA (mg/m ³)	1800 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	3000 ppm (calculated)
Latvia	OEL TWA (mg/m ³)	1800 mg/m ³
Latvia	OEL TWA (ppm)	1000 ppm

	SAFETY DATA SHEET	Page : 8 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

propane (74-98-6)		
Poland	NDS (mg/m ³)	1800 mg/m ³
Portugal	OEL TWA (ppm)	1000 ppm
Romania	OEL TWA (mg/m ³)	1400 mg/m ³
Romania	OEL TWA (ppm)	778 ppm
Romania	OEL STEL (mg/m ³)	1800 mg/m ³
Romania	OEL STEL (ppm)	1000 ppm
Slovenia	OEL TWA (mg/m ³)	1800 mg/m ³
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m ³)	7200 mg/m ³
Slovenia	OEL STEL (ppm)	4000 ppm
Norway	Grenseverdier (AN) (mg/m ³)	900 mg/m ³
Norway	Grenseverdier (AN) (ppm)	500 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	1125 mg/m ³ (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	625 ppm (value calculated)
Switzerland	VME (mg/m ³)	1800 mg/m ³
Switzerland	VME (ppm)	1000 ppm
Switzerland	VLE (mg/m ³)	7200 mg/m ³
Switzerland	VLE (ppm)	4000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1800 mg/m ³
Canada (Quebec)	VEMP (ppm)	1000 ppm
USA - IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
xylene (1330-20-7)		
EU	IOELV TWA (mg/m ³)	221 mg/m ³ (pure)
EU	IOELV TWA (ppm)	50 ppm (pure)
EU	IOELV STEL (mg/m ³)	442 mg/m ³ (pure)
EU	IOELV STEL (ppm)	100 ppm (pure)
Austria	MAK (mg/m ³)	221 mg/m ³ (all isomers)
Austria	MAK (ppm)	50 ppm (all isomers)
Austria	MAK Short time value (mg/m ³)	442 mg/m ³ (all isomers)
Austria	MAK Short time value (ppm)	100 ppm (all isomers)
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	442 mg/m ³
Belgium	Short time value	100 ppm
Bulgaria	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Bulgaria	OEL TWA (ppm)	50 ppm (pure)
Bulgaria	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Bulgaria	OEL STEL (ppm)	100 ppm (pure)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	221 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	442 mg/m ³

	SAFETY DATA SHEET	Page : 9 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

xylene (1330-20-7)		
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
Cyprus	OEL TWA (mg/m ³)	221 mg/m ³
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m ³)	442 mg/m ³
Cyprus	OEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	109 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Estonia	OEL TWA (mg/m ³)	221 mg/m ³
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m ³)	442 mg/m ³
Estonia	OEL STEL (ppm)	100 ppm
Finland	HTP-arvo (8h) (mg/m ³)	220 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
France	VME (mg/m ³)	221 mg/m ³ (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
France	VLE (mg/m ³)	442 mg/m ³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	440 mg/m ³ (all isomers)
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm (all isomers)
Germany	TRGS 903 (BGW)	1,5 mg/l Parameter: Xylene - Medium: whole blood - Sampling time: end of shift (all isomers) 2000 mg/l Parameter: Methylhippuric(tolur-)acid - Medium: urine - Sampling time: end of shift (all isomers)
Gibraltar	8h mg/m ³	221 mg/m ³ (pure)
Gibraltar	8h ppm	50 ppm (pure)
Gibraltar	Short-term mg/m ³	442 mg/m ³ (pure)
Gibraltar	Short-term ppm	100 ppm (pure)
Greece	OEL TWA (mg/m ³)	435 mg/m ³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m ³)	650 mg/m ³
Greece	OEL STEL (ppm)	150 ppm
Hungary	AK-érték	221 mg/m ³
Hungary	CK-érték	442 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	221 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	442 mg/m ³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Italy	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Italy	OEL TWA (ppm)	50 ppm (pure)

	SAFETY DATA SHEET	Page : 10 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

xylene (1330-20-7)		
Italy	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Italy	OEL STEL (ppm)	100 ppm (pure)
Latvia	OEL TWA (mg/m ³)	221 mg/m ³
Latvia	OEL TWA (ppm)	50 ppm
Lithuania	IPRV (mg/m ³)	200 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	450 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Luxembourg	OEL TWA (mg/m ³)	221 mg/m ³
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m ³)	442 mg/m ³
Luxembourg	OEL STEL (ppm)	100 ppm
Malta	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Malta	OEL TWA (ppm)	50 ppm (pure)
Malta	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Malta	OEL STEL (ppm)	100 ppm (pure)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	210 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	442 mg/m ³
Poland	NDS (mg/m ³)	100 mg/m ³
Portugal	OEL TWA (mg/m ³)	221 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)
Portugal	OEL STEL (mg/m ³)	442 mg/m ³ (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Romania	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Romania	OEL TWA (ppm)	50 ppm (pure)
Romania	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Romania	OEL STEL (ppm)	100 ppm (pure)
Slovakia	NPHV (priemerná) (mg/m ³)	221 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	442 mg/m ³
Slovenia	OEL TWA (mg/m ³)	221 mg/m ³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m ³)	442 mg/m ³
Slovenia	OEL STEL (ppm)	100 ppm
Spain	VLA-ED (mg/m ³)	221 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value)
Spain	VLA-EC (mg/m ³)	442 mg/m ³
Spain	VLA-EC (ppm)	100 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	221 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	442 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m ³)	220 mg/m ³

	SAFETY DATA SHEET	Page : 11 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

xylene (1330-20-7)		
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	441 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
Norway	Grenseverdier (AN) (mg/m ³)	108 mg/m ³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	135 mg/m ³ (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	37,5 ppm (value calculated)
Switzerland	VME (mg/m ³)	435 mg/m ³
Switzerland	VME (ppm)	100 ppm
Switzerland	VLE (mg/m ³)	870 mg/m ³
Switzerland	VLE (ppm)	200 ppm
Australia	TWA (mg/m ³)	350 mg/m ³
Australia	TWA (ppm)	80 ppm
Australia	STEL (mg/m ³)	655 mg/m ³
Australia	STEL (ppm)	150 ppm
Canada (Quebec)	VECD (mg/m ³)	651 mg/m ³
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m ³)	434 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
butane (106-97-8)		
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	800 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³
Austria	MAK Short time value (ppm)	1600 ppm
Belgium	Limit value (ppm)	1000 ppm (gas)
Bulgaria	OEL TWA (mg/m ³)	1900 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	1450 mg/m ³ 22 mg/m ³ (containing >=0.1% 1,3-Butadiene)
Croatia	GVI (granična vrijednost izloženosti) (ppm)	600 ppm 10 ppm (containing >=0.1% 1,3-Butadiene)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	1810 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	750 ppm
Denmark	Grænseværdie (langvarig) (mg/m ³)	1200 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Estonia	OEL TWA (mg/m ³)	1500 mg/m ³
Estonia	OEL TWA (ppm)	800 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2400 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1000 ppm

	SAFETY DATA SHEET	Page : 12 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

butane (106-97-8)		
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	800 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	2400 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Greece	OEL TWA (mg/m ³)	2350 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Hungary	AK-érték	2350 mg/m ³
Hungary	CK-érték	9400 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	3000 ppm (calculated)
Latvia	OEL TWA (mg/m ³)	300 mg/m ³
Poland	NDS (mg/m ³)	1900 mg/m ³
Poland	NDSch (mg/m ³)	3000 mg/m ³
Slovenia	OEL TWA (mg/m ³)	2400 mg/m ³ (containing >=0.1% Butadiene)
Slovenia	OEL TWA (ppm)	1000 ppm (containing >=0.1% Butadiene)
Slovenia	OEL STEL (mg/m ³)	9600 mg/m ³ (containing >=0.1% Butadiene)
Slovenia	OEL STEL (ppm)	4000 ppm (containing >=0.1% Butadiene)
United Kingdom	WEL TWA (mg/m ³)	1450 mg/m ³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m ³)	1810 mg/m ³
United Kingdom	WEL STEL (ppm)	750 ppm
Norway	Grenseverdier (AN) (mg/m ³)	600 mg/m ³
Norway	Grenseverdier (AN) (ppm)	250 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	750 mg/m ³ (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	312,5 ppm (value calculated)
Switzerland	VME (mg/m ³)	1900 mg/m ³
Switzerland	VME (ppm)	800 ppm
Switzerland	VLE (mg/m ³)	7600 mg/m ³
Switzerland	VLE (ppm)	3200 ppm
Australia	TWA (mg/m ³)	1900 mg/m ³
Australia	TWA (ppm)	800 ppm
Canada (Quebec)	VEMP (mg/m ³)	1900 mg/m ³
Canada (Quebec)	VEMP (ppm)	800 ppm
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
n-butyl acetate (123-86-4)		
Austria	MAK (mg/m ³)	480 mg/m ³ (all isomers except tert-Butyl acetate)
Austria	MAK (ppm)	100 ppm (all isomers except tert-Butyl acetate)
Austria	MAK Short time value (mg/m ³)	480 mg/m ³ (all isomers except tert-Butyl acetate)
Austria	MAK Short time value (ppm)	100 ppm (all isomers except tert-Butyl acetate)
Austria	OEL - Ceilings (mg/m ³)	480 mg/m ³
Austria	OEL - Ceilings (ppm)	100 ppm

	SAFETY DATA SHEET	Page : 13 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

n-butyl acetate (123-86-4)		
Belgium	Limit value (mg/m ³)	723 mg/m ³
Belgium	Limit value (ppm)	150 ppm
Belgium	Short time value (mg/m ³)	964 mg/m ³
Belgium	Short time value	200 ppm
Bulgaria	OEL TWA (mg/m ³)	710 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	950 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	724 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	150 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	966 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	200 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	950 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	710 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	150 ppm
Finland	HTP-arvo (8h) (mg/m ³)	720 mg/m ³
Finland	HTP-arvo (8h) (ppm)	150 ppm
Finland	HTP-arvo (15 min)	960 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	200 ppm
France	VME (mg/m ³)	710 mg/m ³
France	VME (ppm)	150 ppm
France	VLE (mg/m ³)	940 mg/m ³
France	VLE (ppm)	200 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	300 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	62 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece	OEL TWA (mg/m ³)	710 mg/m ³
Greece	OEL TWA (ppm)	150 ppm
Greece	OEL STEL (mg/m ³)	950 mg/m ³
Greece	OEL STEL (ppm)	200 ppm
Hungary	AK-érték	950 mg/m ³
Hungary	CK-érték	950 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	710 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	150 ppm
Ireland	OEL (15 min ref) (mg/m ³)	950 mg/m ³
Ireland	OEL (15 min ref) (ppm)	200 ppm
Latvia	OEL TWA (mg/m ³)	200 mg/m ³
Poland	NDS (mg/m ³)	200 mg/m ³
Poland	NDSch (mg/m ³)	950 mg/m ³
Portugal	OEL TWA (ppm)	150 ppm
Portugal	OEL STEL (ppm)	200 ppm
Romania	OEL TWA (mg/m ³)	715 mg/m ³
Romania	OEL TWA (ppm)	150 ppm
Romania	OEL STEL (mg/m ³)	950 mg/m ³

	SAFETY DATA SHEET	Page : 14 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

n-butyl acetate (123-86-4)		
Romania	OEL STEL (ppm)	200 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	480 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	700 mg/m ³
Slovenia	OEL TWA (mg/m ³)	480 mg/m ³
Slovenia	OEL TWA (ppm)	100 ppm
Slovenia	OEL STEL (mg/m ³)	480 mg/m ³
Slovenia	OEL STEL (ppm)	100 ppm
Spain	VLA-ED (mg/m ³)	724 mg/m ³
Spain	VLA-ED (ppm)	150 ppm
Spain	VLA-EC (mg/m ³)	965 mg/m ³
Spain	VLA-EC (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	500 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	100 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	700 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	150 ppm
United Kingdom	WEL TWA (mg/m ³)	724 mg/m ³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m ³)	966 mg/m ³
United Kingdom	WEL STEL (ppm)	200 ppm
Switzerland	VME (mg/m ³)	480 mg/m ³
Switzerland	VME (ppm)	100 ppm
Switzerland	VLE (mg/m ³)	960 mg/m ³
Switzerland	VLE (ppm)	200 ppm
Australia	TWA (mg/m ³)	713 mg/m ³
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m ³)	950 mg/m ³
Australia	STEL (ppm)	200 ppm
Canada (Quebec)	VECD (mg/m ³)	950 mg/m ³
Canada (Quebec)	VECD (ppm)	200 ppm
Canada (Quebec)	VEMP (mg/m ³)	713 mg/m ³
Canada (Quebec)	VEMP (ppm)	150 ppm
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - IDLH	US IDLH (ppm)	1700 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	710 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	950 mg/m ³
USA - NIOSH	NIOSH REL (STEL) (ppm)	200 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	150 ppm
Ethyl 3-ethoxypropanoate (763-69-9)		
Austria	MAK (mg/m ³)	610 mg/m ³
Austria	MAK (ppm)	100 ppm
Austria	MAK Short time value (mg/m ³)	610 mg/m ³

	SAFETY DATA SHEET	Page : 15 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

Ethyl 3-ethoxypropanoate (763-69-9)		
Austria	MAK Short time value (ppm)	100 ppm
Austria	OEL - Ceilings (mg/m ³)	610 mg/m ³
Austria	OEL - Ceilings (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	150 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	610 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Switzerland	VME (mg/m ³)	610 mg/m ³
Switzerland	VME (ppm)	100 ppm
Switzerland	VLE (mg/m ³)	610 mg/m ³
Switzerland	VLE (ppm)	100 ppm
ethylbenzene (100-41-4)		
EU	IOELV TWA (mg/m ³)	442 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	884 mg/m ³
EU	IOELV STEL (ppm)	200 ppm
Austria	MAK (mg/m ³)	440 mg/m ³
Austria	MAK (ppm)	100 ppm
Austria	MAK Short time value (mg/m ³)	880 mg/m ³
Austria	MAK Short time value (ppm)	200 ppm
Belgium	Limit value (mg/m ³)	442 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m ³)	551 mg/m ³
Belgium	Short time value	125 ppm
Bulgaria	OEL TWA (mg/m ³)	435 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	545 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	442 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	884 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	200 ppm
Cyprus	OEL TWA (mg/m ³)	442 mg/m ³
Cyprus	OEL TWA (ppm)	100 ppm
Cyprus	OEL STEL (mg/m ³)	884 mg/m ³
Cyprus	OEL STEL (ppm)	200 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	217 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Estonia	OEL TWA (mg/m ³)	442 mg/m ³
Estonia	OEL TWA (ppm)	100 ppm
Estonia	OEL STEL (mg/m ³)	884 mg/m ³
Estonia	OEL STEL (ppm)	200 ppm
Finland	HTP-arvo (8h) (mg/m ³)	220 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm

	SAFETY DATA SHEET	Page : 16 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

ethylbenzene (100-41-4)		
Finland	HTP-arvo (15 min)	880 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	200 ppm
France	VME (mg/m ³)	88,4 mg/m ³ (restrictive limit)
France	VME (ppm)	20 ppm (restrictive limit)
France	VLE (mg/m ³)	442 mg/m ³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	88 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 (BGW)	300 mg/g Parameter: Mandelic acid plus Phenylglyoxylic acid - Medium: urine - Sampling time: end of shift
Gibraltar	8h mg/m ³	442 mg/m ³
Gibraltar	8h ppm	100 ppm
Gibraltar	Short-term mg/m ³	884 mg/m ³
Gibraltar	Short-term ppm	200 ppm
Greece	OEL TWA (mg/m ³)	435 mg/m ³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m ³)	545 mg/m ³
Greece	OEL STEL (ppm)	125 ppm
Hungary	AK-érték	442 mg/m ³
Hungary	CK-érték	884 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	442 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m ³)	884 mg/m ³
Ireland	OEL (15 min ref) (ppm)	200 ppm
Italy	OEL TWA (mg/m ³)	442 mg/m ³
Italy	OEL TWA (ppm)	100 ppm
Italy	OEL STEL (mg/m ³)	884 mg/m ³
Italy	OEL STEL (ppm)	200 ppm
Latvia	OEL TWA (mg/m ³)	442 mg/m ³
Latvia	OEL TWA (ppm)	100 ppm
Lithuania	IPRV (mg/m ³)	442 mg/m ³
Lithuania	IPRV (ppm)	100 ppm
Lithuania	TPRV (mg/m ³)	884 mg/m ³
Lithuania	TPRV (ppm)	200 ppm
Luxembourg	OEL TWA (mg/m ³)	442 mg/m ³
Luxembourg	OEL TWA (ppm)	100 ppm
Luxembourg	OEL STEL (mg/m ³)	884 mg/m ³
Luxembourg	OEL STEL (ppm)	200 ppm
Malta	OEL TWA (mg/m ³)	442 mg/m ³
Malta	OEL TWA (ppm)	100 ppm

	SAFETY DATA SHEET	Page : 17 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

ethylbenzene (100-41-4)		
Malta	OEL STEL (mg/m ³)	884 mg/m ³
Malta	OEL STEL (ppm)	200 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	215 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	430 mg/m ³
Poland	NDS (mg/m ³)	200 mg/m ³
Poland	NDSch (mg/m ³)	400 mg/m ³
Portugal	OEL TWA (mg/m ³)	442 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	100 ppm (indicative limit value)
Portugal	OEL STEL (mg/m ³)	884 mg/m ³ (indicative limit value)
Portugal	OEL STEL (ppm)	200 ppm (indicative limit value)
Romania	OEL TWA (mg/m ³)	442 mg/m ³
Romania	OEL TWA (ppm)	100 ppm
Romania	OEL STEL (mg/m ³)	884 mg/m ³
Romania	OEL STEL (ppm)	200 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	442 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	884 mg/m ³
Slovenia	OEL TWA (mg/m ³)	442 mg/m ³
Slovenia	OEL TWA (ppm)	100 ppm
Slovenia	OEL STEL (mg/m ³)	884 mg/m ³
Slovenia	OEL STEL (ppm)	200 ppm
Spain	VLA-ED (mg/m ³)	441 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	100 ppm (indicative limit value)
Spain	VLA-EC (mg/m ³)	884 mg/m ³
Spain	VLA-EC (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	220 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	884 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m ³)	441 mg/m ³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m ³)	552 mg/m ³
United Kingdom	WEL STEL (ppm)	125 ppm
Norway	Grenseverdier (AN) (mg/m ³)	20 mg/m ³
Norway	Grenseverdier (AN) (ppm)	5 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	30 mg/m ³ (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	10 ppm (value calculated)
Switzerland	VME (mg/m ³)	220 mg/m ³
Switzerland	VME (ppm)	50 ppm
Switzerland	VLE (mg/m ³)	220 mg/m ³
Switzerland	VLE (ppm)	50 ppm
Australia	TWA (mg/m ³)	434 mg/m ³
Australia	TWA (ppm)	100 ppm
Australia	STEL (mg/m ³)	543 mg/m ³
Australia	STEL (ppm)	125 ppm

	SAFETY DATA SHEET	Page : 18 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

ethylbenzene (100-41-4)		
Canada (Quebec)	VECD (mg/m ³)	543 mg/m ³
Canada (Quebec)	VECD (ppm)	125 ppm
Canada (Quebec)	VEMP (mg/m ³)	434 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - IDLH	US IDLH (ppm)	800 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
USA - NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Additional information : Personal air monitoring :. Room air monitoring. Monitoring methods

8.2. Exposure controls

Engineering measure(s)	: Provide adequate ventilation. Organisational measures to prevent /limit releases, dispersion and exposure. Safe handling: see section 7 . Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Store locked up.
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Chemical resistant gloves (according to European standard NF EN 374 or equivalent). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Suitable material: Silver shield ® / 4H® (PE/EVAL/PE). Breakthrough time : >8h
Eye protection	: Use suitable eye protection (EN166): Safety glasses. tightly fitting safety goggles
Body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK + P. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: aerosol.
Colour	: Silver.
Odour	: Not determined.
Odour threshold	: Not determined
pH	: Not determined
Relative evaporation rate (butylacetate=1)	: No data available

	SAFETY DATA SHEET	Page : 19 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

Melting / freezing point	: Not determined
Freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: < 18 °C
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: > 1 mmHg (Ether = 1)
Vapour density	: No data available
Relative density	: 0,755
Solubility	: No data available. Water: Negligible.
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: Not determined
Dynamic viscosity	: Not determined
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: Not determined

9.2. Other information

VOC content	: 42,38 % (weight)
-------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Reference to other sections 10.4 & 10.5.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

Will ignite if exposed to intensive heat and air. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid temperature above 50.
Safe handling: see section 7.

10.5. Incompatible materials

oxidising substances. Safe handling: see section 7.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified (Based on available data, the classification criteria are not met.)
----------------	--

acetone, propan-2-one, propanone (67-64-1)	
LD50/oral/rat	5800 mg/kg
LD50/dermal/rat	> 10000 mg/kg
LD50/dermal/rabbit	> 15700 mg/kg
LC50/inhalation/4h/rat	50100 mg/m ³ (Exposure time: 8 h)

	SAFETY DATA SHEET	Page : 20 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

propane (74-98-6)	
LC50/inhalation/4h/rat	658 mg/l/4h
xylene (1330-20-7)	
LD50/oral/rat	3500 mg/kg
butane (106-97-8)	
LC50/inhalation/4h/rat	658 g/m ³ (Exposure time: 4 h)
n-butyl acetate (123-86-4)	
LD50/oral/rat	10768 mg/kg
LD50/dermal/rabbit	> 17600 mg/kg
LC50/inhalation/4h/rat (ppm)	390 ppm/4h
Ethyl 3-ethoxypropanoate (763-69-9)	
LD50/oral/rat	5 g/kg
LD50/dermal/rabbit	> 9500 mg/kg
LC50/inhalation/4h/rat	> 5,96 mg/l (Exposure time: 6 h)
ethylbenzene (100-41-4)	
LD50/oral/rat	3500 mg/kg
LD50/dermal/rabbit	15400 mg/kg
LC50/inhalation/4h/rat	17,4 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: Not determined
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not determined
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met.)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met.)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met.)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met.)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met.)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met.)

Verado Silver Enamel Spray Paint	
Vaporizer	Aerosol

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

acetone, propan-2-one, propanone (67-64-1)	
LC50 fish 1	4,74 - 6,33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
xylene (1330-20-7)	
LC50 fish 1	13,4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3,82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2,661 - 4,093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0,6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

	SAFETY DATA SHEET	Page : 21 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

n-butyl acetate (123-86-4)	
LC50 fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Ethyl 3-ethoxypropanoate (763-69-9)	
LC50 fish 1	62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	970 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ethylbenzene (100-41-4)	
LC50 fish 1	11,0 - 18,0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1,8 - 2,4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4,2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

12.2. Persistence and degradability

Verado Silver Enamel Spray Paint	
Persistence and degradability	No data available.
n-butyl acetate (123-86-4)	
Biodegradation	83 % (28 days)

12.3. Bioaccumulative potential

Verado Silver Enamel Spray Paint	
Partition coefficient n-octanol/water	No data available
acetone, propan-2-one, propanone (67-64-1)	
BCF fish 1	0,69
Partition coefficient n-octanol/water	-0,24
propane (74-98-6)	
Partition coefficient n-octanol/water	2,3
xylene (1330-20-7)	
BCF fish 1	0,6 - 15
Partition coefficient n-octanol/water	2,77 - 3,15
butane (106-97-8)	
Partition coefficient n-octanol/water	2,89
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water	1,81 (at 23 °C)
Ethyl 3-ethoxypropanoate (763-69-9)	
Partition coefficient n-octanol/water	1,35
ethylbenzene (100-41-4)	
BCF fish 1	15
Partition coefficient n-octanol/water	3,2

12.4. Mobility in soil

Verado Silver Enamel Spray Paint	
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Additional information : No data available

	SAFETY DATA SHEET	Page : 22 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Do not allow to enter into surface water or drains. Dispose of empty containers and wastes safely. Safe handling: see section 7. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.
Additional information	: Never use pressure to empty container. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Do not burn, or use a cutting torch on, the empty drum. Do not puncture or incinerate.
European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC)	: This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1950	1950	1950	1950	1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR)	: 5F
Special provisions	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2

	SAFETY DATA SHEET	Page : 23 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12

Special provisions for carriage - Operation (ADR) : S2

Tunnel restriction code : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

MFAG-No : 126

- Air transport

PCA Excepted quantities (IATA) : E0

PCA Limited quantities (IATA) : Y203

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 203

PCA max net quantity (IATA) : 75kg

CAO packing instructions (IATA) : 203

CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

- Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP02

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

	SAFETY DATA SHEET	Page : 24 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

Special provisions for carriage – Packages : W14
(RID)

Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12

Colis express (express parcels) (RID) : CE2

Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Verado Silver Enamel Spray Paint - acetone, propan-2-one, propanone - xylene - n-butyl acetate - ethylbenzene
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Verado Silver Enamel Spray Paint - acetone, propan-2-one, propanone - xylene - n-butyl acetate - ethylbenzene
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Verado Silver Enamel Spray Paint - acetone, propan-2-one, propanone - xylene - ethylbenzene
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	acetone, propan-2-one, propanone - propane - xylene - butane - n-butyl acetate - ethylbenzene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 42,38 % (weight)

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4320.text	Aérosols extrêmement inflammables ou inflammables de catégorie 1 ou 2 contenant des gaz inflammables de catégorie 1 ou 2 ou des liquides inflammables de catégorie 1.		
4320.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 150 t Nota. — Les aérosols inflammables sont classés conformément à la directive 75/324/CEE relative aux générateurs aérosols. Les aérosols extrêmement inflammables et inflammables de la directive 75/324/ CEE correspondent respectivement aux aérosols inflammables des catégories 1 et 2 du règlement (CE) n° 1272/2008. Quantité seuil bas au sens de l'article R. 511-10 : 150 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	A	2

	SAFETY DATA SHEET	Page : 25 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

4320.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 15 t et inférieure à 150 t Nota. — Les aérosols inflammables sont classés conformément à la directive 75/324/ CEE relative aux générateurs aérosols. Les aérosols extrêmement inflammables et inflammables de la directive 75/324/ CEE correspondent respectivement aux aérosols inflammables des catégories 1 et 2 du règlement (CE) n° 1272/2008. Quantité seuil bas au sens de l'article R. 511-10 : 150 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	D	
--------	---	---	--

Germany

VwVwS Annex reference	: Water hazard class (WGK) 2, hazard to waters (Classification according to VwVwS, Annex 4)
German storage class (LGK)	: LGK 2B - Aerosols
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: xylene is listed

Denmark

Class for fire hazard	: Class I-1
Store unit	: 1 liter
Classification remarks	: F <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed

15.2. Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Indication of changes:

1.1	Document no.	Modified	
1.2	Uses advised against	Added	
2	DSD/DPD	Removed	
2		Modified	
3	Composition	Modified	
3	DSD/DPD	Removed	
4.2	Effects - Symptoms	Modified	
5.2		Modified	
5.3		Modified	
7.2	Special rules on packaging	Removed	
8.1		Modified	
8.2	Eye protection	Modified	
8.2	Hand protection	Added	

	SAFETY DATA SHEET	Page : 26 / 27
		Revision nr : 1.1
		Issue date : 02/03/2017
	Verado Silver Enamel Spray Paint	Supersedes : 28/04/2015
		766-01-0329S

9.1	Physical and chemical properties	Modified	
9.2	VOC	Modified	
11.1		Modified	
12.1		Modified	
14.1		Modified	
15	REACH Annex XVII	Modified	
15	Installations classées	Added	
15.1	Wassergefährungsklasse (WGK)=	Modified	
15.1	German storage class (LGK)	Added	
15.1	Denmark	Added	
16	Other information	Modified	

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time :
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No-Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds (VOC) :
	WGK = Wassergefährungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet : ECHA (European Chemicals Agency), supplier sds, Loli, Inchem.

Training advice : Training staff on good practice.

Other information : Assessment/classification CLP. Article 9. Calculation method.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1

	SAFETY DATA SHEET	Page : 27 / 27
		Revision nr : 1.1
	Verado Silver Enamel Spray Paint	Issue date : 02/03/2017
		Supersedes : 28/04/2015
		766-01-0329S

Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Gas 1	Flammable gases, hazard category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container. May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.